



0910UK

## Smoke Alarm

The 0910UK is the ideal smoke alarm combining long-life, peace-of-mind protection with high-specification features and benefits.



10 Year Warranty



Alarm Hush Feature



Tamper Proof



BS 5446 Part 1: 2009  
License No. 0387081



# 0910UK

## Smoke Alarm

### KEY PRODUCT FEATURES

- Warranted 10 year long-life lithium power cell – for worry free protection.
- Sealed-in power source – reduced user-maintenance. No battery removal or theft problems.
- End-of-life battery warning – gives clear indication of when unit needs replacing at end-of-life.
- Red hush button – easily identified feature to temporarily silence a nuisance alarm. Aids operation of alarm test and hush facilities by the visually impaired.
- Easily adjustable mounting plate – simple for installer to attach plate to wall or ceiling and then connect alarm unit and align for aesthetics.
- Tamper-resist alarm feature – minimises removal of alarm during life-time.
- Self-activation – alarm is activated as soon as attached to mounting plate. This feature ensures users receive full 10 years of alarm life from the time of fitting.
- Deactivation feature – lithium cells can be deactivated after 10 year life-time for safe, environmentally friendly disposal.
- Ionisation technology – quicker at detecting fast-flaming fires.

### SPECIFICATIONS

DESCRIPTION	Long life, sealed power source, tamper-proof smoke alarm
UPC NO	0-047871-059942
PART NO	0910UK
WARRANTY (YRS)	10 (for both the alarm and the battery from activation)
TECHNOLOGY	Ionisation
FEATURES	10 year sealed in lithium battery cells, Hush button feature, Tamper-proof alarm, Easily adjustable mounting plate, Self activation, End-of-life battery warning, Environmental 'deactivation' feature
OPERATION: AC/DC	DC
POWER SOURCE OPERATED	Yes
POWER TYPE	Sealed-in lithium cells (x 3)
PRODUCT WEIGHT	0.20kg
PRODUCT DIMENSIONS	142 x 142 x 40mm (inc. bracket) HxWxD
PERFORMANCE	85 decibels
OPERATING TEMP	40°F (4.4°C) to 100°F (37.8°C)
HUMIDITY RANGE	Up to 85% relative humidity (RH)
INSTALLATION POSITIONS	Wall or Ceiling
APPROVALS	BSI Kitemarked BS 5446 pt 1 : 2000, CE

### PACKING SPECIFICATIONS

INDIVIDUAL	
DIMENSIONS	280 x 185 x 50mm HxWxD
WEIGHT	0.30kg (including packaging)
OUTER	
QTY. PER CASE	3
DIMENSIONS	300 x 195 x 155
WEIGHT	0.95kg

#### Kidde Safety Europe Ltd

Mathisen Way, Poyle Road, Colnbrook, Berkshire SL3 OHB United Kingdom

Tel: +44 (0) 1753 685148 Fax: +44 (0) 1753 685096 www.kiddesafetysafetyeurope.co.uk